INSTALLATION GUIDE

BASIN TABLE 枱面組安裝說明



Assembling main parts with attached Hexagon Key as shown in figure(1).

用六角板手安裝主要的零件,如圖①,



Install Tempered Table Glass as shown in figure 5, placing four Adjusting Holders into holes for fix it. 安裝玻璃檯面,如圖(5).將4個可調整支撐架固定於適當位置.

FIXING CONTENTS

組配件內容



Assembling Towel Rails and 77cm-Length Tubs as shown in figure2.

(2)

h

安裝毛巾桿和77公分長銅管,如圖(2)。

Level Tempered Table Glass by twisting Adjusting Holders. 旋轉在玻璃檯面的可調整支撐架,並調整桌面水平,即完成檯面組裝.



fix Wooden Shelves.

shown in figure(3). Adjust and tighten End Caps for fit and

(3)

ſh

Mark two vertical lines both sides 19.3cm(0.76") from the center of drain outlet, and meantime, using assembled table-keyholes as template or mark and drill two fixing holes for Stainless Steel Wall Screws as shown in figure (7). 用鉛筆在距離牆上排水孔左右各19.3公分處,並在高度61.4公分處畫上2個鎖螺絲的記號, 在畫上記號前,必須注意牆角及地面是否平整且與牆面垂直,並再次確認2記號間與地面 的距離. 崁入塑膠塞並使之齊平於牆面,不要將不銹鋼螺絲全部鎖緊,調整到如圖面所

示的適當位置,螺絲頭與牆面須留2.5mm的距離.



(4)

Screwing Adjusting Holders on Tempered Table Glass(4) 在玻璃檯面上鎖上四個可調整支撐架.

ADJUSTABLE 可調整的



Insert two Stainless Steel Wall Screw heads into keyholes on the back of L & R Side Boards and press downward. Be sure the basin table is flush and tighten to wall (8)

將左.右側腳板後方的孔崁入二處的螺絲頭並且向下按壓,確認腳板是否完全卡緊,並使之齊平 牆面.



JUSTIME | 巧時代 | ST SHENG TAL BRASSWARE CO., LTD.

www.justime.com 150708