## **INSTALLATION GUIDE**

CABINET







Insert the Pins into side of both Upper Wooden Shelf and Lower Wooden Shelf, in the meantime, press and join the two pieces of Wooden Shelves and Wooden Side-Boards together with tenon, then insert Cams into underside-holes of both Upper Wooden Shelf and Lower Wooden Shelf, rotate Cams clockwise and tighten them with attached Hexagon Key. Be sure the two (2) small holes on Wooden Shelves which for install **Cabinet Hinges** are opposite on right-side of the front as shown in figure 2.



Install Cabinet Hinges and Glass Door as shown in figure 3, screw Glass door on appropriate position and tighten securely.



Fix Cabinet Stopper with 4 Fixed Screws onto pre-drill holes, then stick PE Foam-Tape as relative height as Cabinet Stopper, and meantime clamp Clip onto PE Foam-Tape in position as shown in figure 4.



Insert 12 Shelf Supporters into Wooden Side-Board (R) & (L) holes, then install Thick Glass Shelves (a thickness of 6mm) on upper two stories and install Thin Glass Shelf on lower story as shown in figure 5.



Mark two (2) vertical lines 33 cm (13") wide on appropriate position, and meantime mark two (2) drill hole centers as shown in figure 6. Using a 6mm bit, drill screw holes in the positions marked to a depth of 45mm and insert **Plastic Anchors** flush with wall. Do not completely tighten **Wall Screws**, leave 4mm (0.16") space between screw head and wall, adjust if necessary.

## **FIXING CONTENTS**





Insert Two (2) wall screw heads into keyholes on rear of both **Wooden Boards** (R) & (L) and press downward, be sure the cabinet is flush and tighten to wall.

931013 PU08-13-STC0